

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	NORIS Automation GmbH
Address	Friedrich-Barnewitz-Strasse 10, Rostock, 18109, Germany
Type	Transmitters/Transducers
Description	Multifunctional Device designed for: <ul style="list-style-type: none">- Speed Measurement and Signal Processing- Direction of Rotating Detection- Slip Measurement- Offset Measurement
Trade Name	NORISPEED FMN6-1-11-K
Application	Marine, offshore and industrial applications for use in environmental categories ENV1, ENV2, ENV3 and ENV4 as defined in Lloyd's Register's Type Approval System, Test Specification Number 1 – 2002.
Specified Standard	Manufacturer's specification
Ratings	Power Supply: $U_{Nom} = 24 \text{ VDC}$, $U_B = 18 \dots 32 \text{ VDC}$ Input Signal: Pick-Up with PNP, NPN or PushPull Output Measurement Range: 1...12.000 Hz Speed Range: 1...10.000 rpm (depending on impulses/rotation) Max.Impulse/ Rotation: 4...500 Impulses(depending on max. speed) Two galvanic isolated, short-circuit-proof analogue outputs

Thorsten Wolff

Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Output Voltage: 0...5, -5...5, 0...10 or -10...+10 VDC
Output Current: 0...20 or 4...20 mA
Output Relays: 6 floating relay outputs, max.30 VDC/2 A

Additional Tests

Low temperature test: -25°C/ 16h
Mechanical shock test: half sine, 15g, 11ms
Number of load planes: 6 ($\pm X$, $\pm Y$ and $\pm Z$)
Number of shocks per load plane: 3 (in total 18)

Other Conditions

Final functional arrangements are to comply with appropriate Lloyd's Register Rules and will be subject of the Plan Approval process, if applicable.
LR Software Conformity Assessment is not a part of this Type Approval and therefore every application of NORISPEED FMN6-1-11-K is to be examined for compliance with LR requirements for programmable electronic systems implementing emergency stop or safety critical functions.
Equipment has to comply with IACS E10 Rev.7 when intended to be installed on ships contracted for construction on or after 1 January 2022.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: 12/20014 (E1)

The Design Appraisal Document HTS/ETS 40938-21/TW and its supplementary Type Approval Terms and Conditions form part of this Certificate.