



TYPE APPROVAL CERTIFICATE

Certificate no.:
TAA00002E8
Revision No:
1

This is to certify:
that the Pressure Transmitter

with type designation(s)
PAA9-..., PAG9-...

issued to
NORIS Automation GmbH
Nürnberg, Bayern, Germany

is found to comply with
DNV rules for classification – Ships, offshore units, and high speed and light craft

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Location classes:

Temperature	D
Humidity	B
Vibration	B
EMC	B
Enclosure	C

Issued at **Hamburg** on **2024-06-06**

for **DNV**

This Certificate is valid until **2027-12-19**.

DNV local unit: **Augsburg**

Approval Engineer: **Holger Jansen**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Pressure transmitter for absolute and relative pressure measurement.

Type: PAA9-... (absolute)
PAG9-... (relative)

Sensor: Thin-film on steel or piezo-resistive
Measuring ranges: 0...0.6 to 0...600 bar

Output signal / [Power supply]:
▪ Current (2-wire): 4...20 mA / [DC 24 V (8...30 V)]
▪ Voltage (3-wire): DC 0...10 V / [DC 24 V (14...30 V)]

Electrical connection:
▪ Angular connector (DIN EN 175 301-803 A)
▪ Circular connector (M12x1)
▪ Cable outlet: OEM, UL 94 V-0 listed, max. length 5 m

Process connection:
▪ G1/4", M14x1.5, 1/4 NPT
▪ Material (sensor, housing): stainless steel 316L

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems.

Degree of protection: IP65 / IP 67 (M12x1 and cable outlet)

Type Approval documentation

Technical- and Test documentation:
Ref: 12AR-01026 / No. PRQ00045623
Instruction Manual Pax9 No. NAN-KD-0030-en_V01.01, 2016-03-02
Drawings: no. 50.810, 50.811, 50.812 of 2015-06-24
Type Approval Assessment Report dated 2024-05-22

Tests carried out

Applicable tests according to DNV Class Guideline CG0339, August 2021.

Additional tests: Vibration: 20g, sinus (25...2000Hz)
Cold: -30 °C
Dry Heat: +100°C

Marking of product

The products to be marked with:

- Manufacturer name
- Model name
- Serial number
- Power supply ratings

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE